

Industrial confidentiality

## PRODUCT SPECIFICATION

Product code:

IXF-RAD-AMP-2

	Parameter	Specification	Units
1	Absorption @ 1530 nm	25 ±3	dB/m
2	Absorption @ 980 nm	17 ±2	dB/m
3	MFD @ 1550 nm	5.5 ±1	µm
4	Background losses	< 20	dB/km
5	Cutoff Wavelength	< 1150	nm
6	Cladding Diameter	125 ±2	µm
7	Coating Diameter	245 ±10	µm
8	Proof test level	100	kpsi
9	Splice Loss (to SMF28)	< 0.20	dB
10	RIA @1545nm	< 0.015	dB/m/kRad
11	RIA @980nm	< 0.025	dB/m/kRad
12	RIGV @1545nm	< 0.03	dB/kRad

### Comments

RIA: Radiation Induced Attenuation

RIGV: Radiation Induced Gain Variation

RIGV has been measured in amplifier configuration with -20dBm 1545nm input signal and 100mW 976nm constant forward pumping (fiber length = 6m)

Effective date of this document: 06/04/2018

Edition: B

Document reference: IXF-RAD-AMP-2\_edB.pdf

*Specifications are subject to change without notice*

PSD-L-Q-E-086-I

